

# SKARE SHELTER Design: HITSA

 $\label{eq:modular-extra} \mbox{Modular-extra bays can be added to extend the shelter} \mbox{ Depth: } 4200 \mbox{ mm}$ 



## SKARE SHELTER

- Modular extra bays can be added to extend the shelter (bays up to 4 metres)
- Depth: 4200 mm
- Optional extra: Steel guttering and drainpipe down to the ground
- $\bullet \quad \hbox{Optional extra: Side panels, $1$-4 sides, and/or central panels}$
- Optional extra: Sliding door(s)
- Optional extra: LED lighting

## MATERIALS:

- Hot-dip galvanised steel
- Also available in powder-coated, hot-dip galvanised steel.
  The following components are not powder-coated: roof panels, roof strip, guttering, drainpipes and aluminium edge strips, any door rails, etc.

#### ROOF TYPES:

• 1.5 mm smooth steel panels, hot-dip galvanised

### PANEL MATERIALS:

- to lower edge of transverse supporting beam
- 2 mm perforated steel panels

## DIMENSIONS:

Columns: Ø 114 mm tubular steel Transverse supporting beam:  $100 \times 50$  mm rectangular profile Arches/rafters:  $60 \times 30$  mm rectangular profile Roof strip:  $50 \times 3$  mm flat steel

#### INSTALLATION:

• To be cemented in on site. Installation according to instructions from HITSA.



