FJORDPARK 4 WASTE BIN

LCA overview

Product: Fjordpark 4 waste bin (embedded mounting)

Scope: A1, A2, A3. GWP = Global Warming Potential

ISO 14021 self-declared results, calculated according to ISO 14040 and ISO 14044 standards.

The results follow EN 15804+A2.

S = side throw, P = perforated, G = smooth, A = ash tray, N = embedded, Galv = hot-dip galvanized steel, Cort = corteen steel, RAL = powder coating

Product name	Description	Side throw(s)	Corteen	RAL	Perforated	Ash tray	Mass of declared unit (kg)	GWP-fossil, A1-A3 (kg CO_2e)	GWP-total, A1-A3 (kg CO_2e)
Fjordpark 4 , 1s-PN,RAL	Hot-dip galvanized, powder coated steel + perforated	1		x	x		66,5	185	183
Fjordpark 4, 1s-GN,RAL	Hot-dip galvanized, powder coated steel			x			70,1	185	183
Fjordpark 4, 1s-PAN,RAL	Hot-dip galvanized, powder coated steel + perforated + ash tray			x	x	x	68,4	194	192
Fjordpark 4, 1s-GAN,RAL	Hot-dip galvanized, powder coated steel + ash tray			x		x	72	194	192
Fjordpark 4, 1s-PN,galv	Hot-dip galvanized steel + perforated				x		64,3	163	162
Fjordpark 4, 1s-GN,galv	Hot-dip galvanized steel						67,8	162	161
Fjordpark 4, 1s-PAN,galv	Hot-dip galvanized steel + perforated + ash tray				x	x	66,2	172	171
Fjordpark 4, 1s-GAN,galv	Hot-dip galvanized steel + ash tray					x	69,7	171	170

LCA overview

Product: Fjordpark 4 waste bin (embedded mounting)

Scope: A1, A2, A3. GWP = Global Warming Potential

ISO 14021 self-declared results, calculated according to ISO 14040 and ISO 14044 standards.

The results follow EN 15804+A2.

S = side throw, P = perforated, G = smooth, A = ash tray, N = embedded, Galv = hot-dip galvanized steel, Cort = corteen steel, RAL = powder coating

Product name	Description	Side throw(s)	Corteen	RAL	Perforated	Ash tray	Mass of declared unit (kg)	GWP-fossil, A1-A3 (kg CO_2e)	GWP-total, A1-A3 (kg CO_2e)
Fjordpark 4, 2s-PN,RAL	Hot-dip galvanized, powder coated steel + perforated	2		x	x		65,6	183	182
Fjordpark 4, 2s-GN,RAL	Hot-dip galvanized, powder coated steel			x			68,6	182	181
Fjordpark 4, 2s-PAN,RAL	Hot-dip galvanized, powder coated steel + perforated + ash tray			x	x	x	67,5	192	191
Fjordpark 4, 2s-GAN,RAL	Hot-dip galvanized, powder coated steel + ash tray			x		x	70,5	191	190
Fjordpark 4, 2s-PN,galv	Hot-dip galvanized steel + perforated				x		63,5	162	161
Fjordpark 4, 2s-GN,galv	Hot-dip galvanized steel						66,4	160	159
Fjordpark 4, 2s-PAN,galv	Hot-dip galvanized steel + perforated + ash tray				x	x	65,4	171	170
Fjordpark 4, 2s-GAN,galv	Hot-dip galvanized steel + ash tray					x	68,3	169	168

LCA overview

Product: Fjordpark 4 waste bin (embedded mounting)

Scope: A1, A2, A3. GWP = Global Warming Potential

ISO 14021 self-declared results, calculated according to ISO 14040 and ISO 14044 standards.

The results follow EN 15804+A2.

S = side throw, P = perforated, G = smooth, A = ash tray, N = embedded, Galv = hot-dip galvanized steel, Cort = corteen steel, RAL = powder coating

Product name	Description	Side throw(s)	Corteen	RAL	Perforated	Ash tray	Mass of declared unit (kg)	GWP-fossil, A1-A3 (kg CO_2e)	GWP-total, A1-A3 (kg CO_2e)
Fjordpark 4, 1s-PN, cort	Corteen steel + perforated	1	x		x		60,5	134	133
Fjordpark 4, 1s-GN, cort	Corteen steel		x				63,7	132	131
Fjordpark 4,1s-PAN, cort	Corteen steel + perforated + ash tray		x		x	x	62,4	143	142
Fjordpark 4, 1s-GAN, cort	Corteen steel + ash tray		x			x	65,6	141	140
Fjordpark 4, 2s-PN, cort	Corteen steel + perforated	2	x		x		59,7	133	132
Fjordpark 4, 2s-GN, cort	Corteen steel		x				62,4	130	129
Fjordpark 4,2s-PAN, cort	Corteen steel + perforated + ash tray		x		x	x	61,6	142	141
Fjordpark 4, 2s-GAN, cort	Corteen steel + ash tray		x			x	64,3	139	138